

PREMIUM COLORS

Slub Solids

RECASENS USA BCN **T** 1886

R-792 Taupe Slub Tweed

47″

Width: **47**"






NEW

47″

R-244 Dun 47″

R-156 Brown 47" / 60"



Tweed Solids

R-776 Taupe Tweed

47″

R-293 Argent T 47"	weed NEW	R-295 Hone 47″	ey Tweed NEW	R-775 Lin 47" / 60"	en Tweed
R-769 Baltic Tweed		R-772 Blue	Tweed	R-313 Iguana Tweed	
47" / 60"	NEW	60" Only		47″	Ν

R-774 Smoke Tweed

47″



*Recacril[®] slub fabrics are visually different from front to back. Either side is usable. Be careful in orientation.



R-773 Red Tweed

60" Only

R-771 Green Tweed 60" Only

47″

R-197 Lead Tweed



47″ NEW



R-294 Ice Tweed

	R-115 Cream 47″	R-180 Sand 47"	R-193 Light Blue 47″	R-169 Steel Blue 47" / 60"	R-296 Lagoon 47" NEW	R-911 Baltic 47" / 60" NEW	R-172 Blue 47" / 60"
	R-300 Oat	R-314 Maple	R-173 Dark Blue	R-229 Sapphire	R-232 Denim	R-170 Admiral Blue	R-174 Navy Blue
	47" NEW		47" / 60"	47"	47"	47" / 60"	47" / 60"
e	R-143 Hemp Beige 47″ / 60″	• R-554 Yellow 47" / 60"	R-175 Captain Navy 47″ / 60″	R-160 Pistachio 47" / 60"	R-187 Jade 47″	R-142 Emerald 47" / 60"	R-292 Teal 47" / 60" NEW
	 R-105 Salmon 47" 	• R-176 Red 47" / 60"	R-163 Green 47" / 60"	R-248 Hunter 47"	R-102 Forest Green 47" / 60"	R-114 Pearl 47" / 60"	R-186 Silver 47″
	R-195 Cacao	R-243 Tapenade	R-196 Titanium	R-138 Cadet Grey	R-161 Grey	R-127 Moonrock	R-194 Ash
	47"	47″	47" / 60"	47" / 60"	47" / 60"	47" / 60"	47" / 60"
	R-181 Coffee	R-171 Turquoise	R-198 Nickel	R-164 Charcoal Grev	R-298 Coal	R-150 Dark Grev	R-103 Black

e R-181 Coffee 47″

R-171 Turquoise 47" / 60"

R-198 Nickel 47" / 60"

R-164 Charcoal Grey 47" / 60"

R-298 Coal 47″

NEW

R-150 Dark Grey 47″

R-103 Black 47" / 60"



Superior performance fabrics

- Tighter weave
- Superior stability
- Unsurpassed fade resistance
- Better to cut and sew
- Proprietary Infinity finishing
 process
- Long lasting water resistance
- Stain resistant
- Backed by 10 year warranty

Awning and Marine Acrylic Fabric

1 i 1 3 🕗 2 9 1

LINE

47" Collection





Technical Specifications

1					
FABRIC TYPE					
Name of Fabric	Recacril®				
Base Fabric	100% Solution dyed acrylic fibers				
CHARACTERISTICS					
Weight	9 oz. +/- 5%				
Standard Put Up	65.64 yards / 60 meters				
Finish	Fluorocarbon / Resin				
Finished Width	47"/ 120 cm				
Styles	73 solids				
Limited Warranty	10 years				
SPECIFICATIONS	TEST RESULTS	TEST METHOD			
UV Resistance	1500 + hours	AATCC-16			
Abrasion Rating	40,000 Rubs	ASTM-4157			
Hydrostatic	40 cm	AATCC-127 Method B			
Puncture Strength	38 lbs	ASTM-751			
	WARP / WEFT				
Tear Strength 11.5 lbs / 7.7 lbs		ASTM D-2261			
Tensile Strength 287 lbs / 149 lbs		ASTM D-5034 Grab			
Shrinkage 0.10% / 0%		Method 5804			
Stretch	0% / 0%	ASTM D-2594			
SAFETY, HEALTH AND ENVIRO	NMENT				
OEKO-TEX		?!! /			
REACH STANDARD 10	00 🏽 🚺 🕰 🖉 🖾 🖉 🖾 🖉				
20110K0127 Al Control de sustancias no					
www.oeko-tex.com/standar					



Care and Cleaning

Proper care and cleaning should be taken to ensure the life of Recacril® outdoor fabrics.

For regular care and maintenance, the excess dirt should be brushed from the fabric using a soft brush; the fabric should then be sprayed with warm water (not exceeding 100° F) and air-dried.

Periodically, the fabric should undergo a more thorough cleaning. Again, brush fabric with a soft bristled brush, spray with warm water, then apply a gentle soap. Let stand for 10 to 20 minutes taking care not to let it dry, then rinse thoroughly and air-dry. Do not use detergents and/or solvents.

When possible, please make sure to leave retractable awnings deployed or extended until the fabric cover is dried completely. This will help prevent mildew from forming.

Infinity Process

The Recacril® and Recsystem® canvases are treated with a special technological process to ensure the lasting quality of the fabric. In this process, nanoparticles completely cover the surface of the fibers in the fabric, forming a permanent coat. After treatment, both the surface and the inside of the fabric are permanently protected against dirt build-up, and adverse effects of a wide variety of atmospheric agents.

The low reactivity and high stability of the Infinity treatment endows longterm protection to the awning, especially against mildew, and provides excellent water and oil repellence.



RECASENS BCN **n** 1886



The technical characteristics shown are average values with a +/-5% tolerance. The data indicated in this document are the result of laboratory tests or technical calculations in accordance with current regulations. As our products are constantly evolving, according to market demands and technical progress, S.A. RECASENS reserves the right to change these data at any time. It is the customer's responsibility to check that the data that they are consulting are from the most recent update. The customer shall be responsibility to check that the data that they are consulting are from the most recent update. The customer shall be responsibility regarding the assembly and installation of its products. It also accepts no responsibility for its products being installation in one-compliance with current regulations. The photographs and descriptions in this catalogue have no contractual value, they are indicated for guidance only, S.A. RECASENS reserves the right to make any modifications it deems appropriate. Copyright02021 S.A. RECASENS, All rights reserved.



customerservices@recasensusa.com www.recasensusa.com